NSN 4720-00-847-8410

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-847-8410

Cross Sectional Shape:
Round
Inside Diameter:
1.375 inches
Tempurature Rating:
-65.0 degrees fahrenheit single response and 250.0 degrees fahrenheit single response
Flange Thickness:
0.359 inches 1st end
Outside Diameter:
1.704 inches
Minimum Inside Bending Radius:
9.000 inches
Exterior Color:
Natural
Center To Center Distance Between Bolt Holes Along Width:
1.812 inches 1st end
Center To Center Distance Between Bolt Holes Along Length:
1.812 inches 1st end
Bolt Hole Quantity:
4 1st end
Flange Length:
2.375 inches 1st end
Flange Width:
2.375 inches 1st end
Connection Style:
Raised swivel 1st end
Bolt Hole Diameter:
0.266 inches 1st end
Raised Face Height:
0.062 inches 1st end
Raised Face Diameter:
2.135 inches 1st end
End Flange Construction:
Solid 1st end
End Connection Design:
Straight 1st end
Connection Type:
Raised face flange 1st end
Features Provided:
Electrostatic discharge capability and internal support

Burst Test Pressure:

1750.0 pounds per square inch

NSN 4720-00-847-8410

Nonmetallic Hose Assembly - Page 2 of 2



Layer Composition And Location:	
Outer layer braided corrosion resistant steel wire	
Maximum Operating Pressure:	
250.0 pounds per square inch	
Hydrostatic Test Pressure:	
800.0 pounds per square inch	
Outer Covering Environmental Protection:	
Corrosion resistant	
Vacuum In Torr:	
203.2	
Inside Surface Condition:	
Smooth	
Measuring Method And Length:	
13.000 inches	
Flange Style:	
Rectangular (includes square) 1st end	
Media For Which Designed:	
Fuel/oil, hydrocarbon single response	
Supplementary Features:	
This item has been reviewed for asbestos material; the current approved sources; 00624 have indicated their part number contained	
asbestos prior to 1984, they continue to manufacture the same part number without asbestos material after 1984	
Specification Data:	
96906-ms87032 government standard	
Shelf Life:	
N/a	
Unit Of Measure:	
	
Demilitarization:	
No	
Fiig:	
A542a0	