## NSN 4720-00-849-7184

**Cross Sectional Shape:** 

N/a

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-849-7184

Round						
Thread Class:						
3b 1st end						
Thread Direction:						
Right-hand 1st end						
Inside Diameter:						
0.188 inches						
Tempurature Rating:						
-65.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response						
Outside Diameter:						
0.312 inches						
Minimum Inside Bending Radius:						
2.000 inches						
Connection Style:						
Swivel nut, flareless 1st end						
End Connection Design:						
Straight 1st end						
Connection Type:						
Threaded internal tube 1st end						
Features Provided:						
Electrostatic discharge capability						
Burst Test Pressure:						
12000.0 pounds per square inch						
Layer Composition And Location:						
Outer layer braided corrosion resistant steel wire						
Maximum Operating Pressure:						
1500.0 pounds per square inch						
Thread Size:						
0.438 inches 1st end						
Seat Angle:						
12.0 degrees 1st end						
Hydrostatic Test Pressure:						
3000.0 pounds per square inch						
Inside Surface Condition:						
Smooth						
Measuring Method And Length:						
21.000 inches working						
Thread Series Designator:						
Unjf 1st end						
Shelf Life:						

## NSN 4720-00-849-7184

Nonmetallic Hose Assembly - Page 2 of 2



	• •				
In	18	<i>(</i> )+	МА	261	ıre:

--

Demilitarization:

No

Fiig:

A542a0