

View Online at <https://aerobasegroup.com/nsn/4720-00-849-8549>

**Cross Sectional Shape:**

Round

**Inside Diameter:**

1.375 inches

**Temperature Rating:**

-65.0 degrees fahrenheit and 160.0 degrees fahrenheit single response

**Flange Thickness:**

0.363 inches and 0.395 inches 1st end

**Outside Diameter:**

1.695 inches

**Minimum Inside Bending Radius:**

11.000 inches

**Center To Center Distance Between Bolt Holes Along Width:**

1.812 inches 1st end

**Center To Center Distance Between Bolt Holes Along Length:**

1.812 inches 1st end

**Bolt Hole Quantity:**

4 1st end

**Flange Length:**

2.375 inches 1st end

**Flange Width:**

2.375 inches 1st end

**Connection Style:**

Raised swivel 1st end

**Bolt Hole Diameter:**

0.266 inches and 0.276 inches 1st end

**Raised Face Height:**

0.020 inches 1st end

**Raised Face Diameter:**

2.125 inches 1st end

**End Flange Construction:**

Solid 1st end

**End Connection Design:**

Straight 1st end

**Connection Type:**

Raised face flange 1st end

**Features Provided:**

Electrostatic discharge capability and reusable end fittings

**Burst Test Pressure:**

720.0 pounds per square inch

**Layer Composition And Location:**

1st layer braided cotton cord and 2nd layer braided steel wire and outer layer rubber impregnated braided cotton cord

**Maximum Operating Pressure:**

120.0 pounds per square inch

**Hydrostatic Test Pressure:**

240.0 pounds per square inch

**Outer Covering Environmental Protection:**

Fuel resistant and hydraulic solution resistant and solvent resistant and water resistant

**Inside Surface Condition:**

Smooth

**Measuring Method And Length:**

22.500 inches

**Flange Style:**

Rectangular (includes square) 1st end

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A542a0