NSN 4720-00-851-5876

Measuring Method And Length:

18.000 inches working

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-851-5876

Cross Sectional Shape:
Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.219 inches
Tempurature Rating:
-65.0 degrees fahrenheit and 400.0 degrees fahrenheit single response
Outside Diameter:
0.500 inches
Minimum Inside Bending Radius:
3.000 inches
Exterior Color:
Natural
Connection Style:
Swivel nut flare 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Features Provided:
Electrostatic discharge capability
Burst Test Pressure:
12000.0 pounds per square inch
Layer Composition And Location:
1st layer braided steel wire and 2nd layer spirally wrapped polytetrafluoroethylene fabric and outer layer braided corrosion resistant steel
wire
Maximum Operating Pressure:
3000.0 pounds per square inch
Thread Size:
0.438 inches 1st end
Seat Angle:
37.0 degrees 1st end
Hydrostatic Test Pressure:
6000.0 pounds per square inch
Outer Covering Environmental Protection:
Corrosion resistant
Inside Surface Condition:
Smooth

NSN 4720-00-851-5876

Nonmetallic Hose Assembly - Page 2 of 2



_		•	_	
ı	hread	Series	1)66	ignator:
•	mcaa	OCI ICS	D C3	igilatoi.

Unf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A542a0