

NSN 4720-00-851-5950 Nonmetallic Hose Assembly - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/4720-00-851-5950 **Cross Sectional Shape:** Round **Thread Class:** 3b 1st end **Thread Direction:**

0.625 inches **Tempurature Rating:** -67.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response **Outside Diameter:** 0.797 inches

Minimum Inside Bending Radius: 6.500 inches

Connection Style:

Swivel nut flare 1st end

Right-hand 1st end **Inside Diameter:**

End Connection Design:

Straight 1st end

Connection Type:

Threaded internal tube 1st end

Features Provided:

Internal support

Thready Qty Per Inch (tpi):

12 1st end

Burst Test Pressure:

5000.0 pounds per square inch

Layer Composition And Location:

Outer layer braided corrosion resistant steel wire

Maximum Operating Pressure:

1000.0 pounds per square inch

Thread Size:

1.062 inches 1st end

Seat Angle:

37.0 degrees 1st end

Hydrostatic Test Pressure:

2000.0 pounds per square inch

Outer Covering Environmental Protection:

Corrosion resistant

Vacuum In Torr:

50.8

Inside Surface Condition:

Smooth

NSN 4720-00-851-5950

Nonmetallic Hose Assembly - Page 2 of 2



| Measuring Method And Length: |
|----------------------------------|
| 22.750 inches |
| Thread Series Designator: |
| Unj 1st end |
| Specification Data: |
| 96906-ms8000 government standard |
| Specification Or Standard: |
| 1 class |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |

Mil-std (military Standard): Mil-h-25579 spec.

A542a0