NSN 4720-00-851-7006



Nonmetallic Hose Assembly - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/4720-00-851-7006 **Cross Sectional Shape:** Round **Thread Class:** 2a 1st end **Thread Direction:** Right-hand 1st end **Inside Diameter:** 0.250 inches **Tempurature Rating:** -40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response **Outside Diameter:** 0.562 inches **Minimum Inside Bending Radius:** 3.000 inches **Connection Style:** Inverted flare 2nd end **End Connection Design:** Straight 2nd end **Connection Type:** Threaded external tube 1st end **Burst Test Pressure:** 5000.0 pounds per square inch **Layer Composition And Location:** 1st layer braided textile yarn and 2nd layer braided textile yarn and outer layer molded rubber, synthetic **Maximum Operating Pressure:** 1250.0 pounds per square inch **Thread Size:** 0.625 inches 1st end Seat Angle: 45.0 degrees 1st end **Inside Surface Condition:** Smooth **Measuring Method And Length:** 12.000 inches Media For Which Designed: Fuel/oil, hydrocarbon single response **Thread Series Designator:** Unf 1st end Shelf Life:

N/a

Unit Of Measure:

NSN 4720-00-851-7006

Nonmetallic Hose Assembly - Page 2 of 2



Demilitarization:

No

Fiig:

A542a0