a 1 of 2 etallic Hos ۸ م Nonm



Nonmetallic Hose Assembly - Page 1 of 2		Group
View Online at https://aerobasegroup.com/nsn/4720-00-852-1125		
Cross Sectional Shape:		
Round		
Thread Class:		
3b 1st end		
Thread Direction:		
Right-hand 1st end		
Inside Diameter:		
0.219 inches		
Tempurature Rating:		
-65.0 degrees fahrenheit and 400.0 degrees fahrenheit single response		
Outside Diameter:		
0.469 inches		
Connection Style:		
Swivel nut flare 1st end		
End Connection Design:		
Straight 1st end		
Connection Type:		
Threaded internal tube 1st end		
Features Provided:		
Electrostatic discharge capability		
Thready Qty Per Inch (tpi):		
20 1st end		
Burst Test Pressure:		
16000.0 pounds per square inch		
Layer Composition And Location:		
1st layer braided steel wire and 2nd layer spirally wrapped polytetrafluoroethylene fabric and outer layer braided co	prrosion resista	int steel
wire		
Maximum Operating Pressure:		
3000.0 pounds per square inch		
Thread Size:		
0.500 inches 1st end		
Seat Angle:		
37.0 degrees 1st end		
Outer Covering Environmental Protection:		
Abrasion resistant		
Inside Surface Condition:		
Smooth		
Measuring Method And Length:		
19.000 inches working		
Thread Series Designator:		

Unf 1st end

Shelf Life:

N/a

Nonmetallic Hose Assembly - Page 2 of 2



Unit Of Measure:

Demilitarization:

No

Fiig:

A542a0