

View Online at <https://aerobasegroup.com/nsn/4720-00-854-5301>

Cross Sectional Shape:

Round

Thread Class:

3a 2nd end

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.188 inches

Outside Diameter:

0.484 inches

Minimum Inside Bending Radius:

3.500 inches

Connection Style:

Inverted flare 2nd end

End Connection Design:

Straight 2nd end

Connection Type:

Threaded internal tube 1st end

Thready Qty Per Inch (tpi):

24 1st end

Burst Test Pressure:

4500.0 pounds per square inch

Layer Composition And Location:

1st layer braided rayon cord and 2nd layer braided rayon cord and outer layer molded rubber, synthetic

Maximum Operating Pressure:

1125.0 pounds per square inch

Thread Size:

0.438 inches 1st end

Seat Angle:

37.0 degrees 2nd end

Outer Covering Environmental Protection:

Cold resistant and hydraulic solution resistant and weatherproof

Inside Surface Condition:

Smooth

Measuring Method And Length:

25.000 inches

Special Features:

First end has bulkhead threads 0.625-18 unf rh, 0.675 in. Thd lg

Media For Which Designed:

Hydraulic fluid single response

Thread Series Designator:

Uns 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0