

View Online at <https://aerobasegroup.com/nsn/4720-00-854-6327>

Cross Sectional Shape:

Round

Thread Class:

3a 2nd end

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.250 inches

Temperature Rating:

-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response

Outside Diameter:

Between 0.656 inches and 0.719 inches

Minimum Inside Bending Radius:

4.000 inches

Exterior Color:

Black

End Application:

International construction equipment, inc; hydraulic control system

Connection Style:

Plain 2nd end

End Connection Design:

Straight 2nd end

Connection Type:

Threaded external tube 2nd end

Thready Qty Per Inch (tpi):

16 2nd end

Burst Test Pressure:

20000.0 pounds per square inch

Layer Composition And Location:

1st layer braided steel wire and 2nd layer braided steel wire and outer layer molded rubber, synthetic

Maximum Operating Pressure:

5000.0 pounds per square inch

Thread Size:

1.125 inches 2nd end

Seat Angle:

45.0 degrees 1st end

Hydrostatic Test Pressure:

10000.0 pounds per square inch

Outer Covering Environmental Protection:

Oil resistant and weatherproof

Inside Surface Condition:

Smooth

Measuring Method And Length:

30.000 inches

Special Features:

Second end furnished with dust cap

Media For Which Designed:

Fuel/oil, hydrocarbon single response

Thread Series Designator:

Unf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A542a0