Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-856-8276

| Cross Sectional Shape:  |
|---|
| Round   |
| Thread Class:   |
| 3b 1st end  |
| Thread Direction:   |
| Right-hand 1st end  |
| Inside Diameter:  |
| 0.188 inches  |
| Tempurature Rating:   |
| -65.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response |
| Outside Diameter:   |
| 0.312 inches  |
| Minimum Inside Bending Radius:  |
| 2.000 inches  |
| Connection Style:   |
| Swivel nut flare 2nd end  |
| End Connection Design:  |
| Straight 1st end  |
| Connection Type:  |
| Threaded internal tube 1st end  |
| Burst Test Pressure:  |
| 12000.0 pounds per square inch  |
| Layer Composition And Location:   |
| Outer layer braided corrosion resistant steel wire                                    |
| Maximum Operating Pressure:   |
| 1500.0 pounds per square inch   |
| Thread Size:  |
| 0.562 inches 2nd end  |
| Seat Angle:   |
| 37.0 degrees 2nd end  |
| Hydrostatic Test Pressure:  |
| 3000.0 pounds per square inch   |
| Flow Angle:   |
| 90.0 degrees 2nd end  |
| Inside Surface Condition:   |
| Smooth  |
| Measuring Method And Length:  |
| 21.000 inches working   |
| Thread Series Designator:   |
| Unjf 1st end  |
| Specification Data:   |
| 96906-ms8005 government standard  |
|   |

## NSN 4720-00-856-8276

Nonmetallic Hose Assembly - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0

