## NSN 4720-00-857-5660

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-857-5660

Cross Sectional Shape:
Round
Thread Class:
3b 2nd end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.313 inches
Tempurature Rating:
-65.0 degrees fahrenheit and 450.0 degrees fahrenheit single response
Outside Diameter:
0.438 inches
Minimum Inside Bending Radius:
4.000 inches
Connection Style:
Swivel nut flare 2nd end
End Fitting Component And Material:
Complete fitting stainless steel all ends
Fitting Component And Surface Treatment:
Complete fitting passivate 1st end
Connection Type:
Threaded internal tube 2nd end
Thready Qty Per Inch (tpi):
18 1st end
Burst Test Pressure:
9000.0 pounds per square inch
Layer Composition And Location:
Outer layer braided corrosion resistant steel wire
Maximum Operating Pressure:
1500.0 pounds per square inch
Seat Angle:
37.0 degrees 2nd end
Hydrostatic Test Pressure:
3000.0 pounds per square inch
Vacuum In Torr:
50.8
Inside Surface Condition:
Smooth
Special Features:
Inner conveying tube material-plastic, polytetrafluoroethylene
Thread Series Designator:
Unjf 2nd end

## NSN 4720-00-857-5660

Nonmetallic Hose Assembly - Page 2 of 2



_					
•	n	<b>0</b> 1	•	12	e:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A542a0