## NSN 4720-00-857-7484

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-857-7484

Cross Sectional Shape:
Round
Thread Class:
2b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.312 inches
Outside Diameter:
0.671 inches
Connection Style:
Swivel nut flare 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Burst Test Pressure:
9000.0 pounds per square inch
Layer Composition And Location:
1st layer braided cotton cord and 2nd layer braided wire and outer layer rubber impregnated braided cotton cord
Maximum Operating Pressure:
2000.0 pounds per square inch
Thread Size:
0.562 inches 1st end
Seat Angle:
37.0 degrees 1st end
Inside Surface Condition:
Smooth
Measuring Method And Length:
11.250 inches working
Media For Which Designed:
Fuel/oil, hydrocarbon single response
Thread Series Designator:
Unf 1st end
Specification Data:
96906-ms28741-6-0112 government standard
Shelf Life:
N/a
Unit Of Measure:
<del></del>
Demilitarization:

No

## NSN 4720-00-857-7484

Nonmetallic Hose Assembly - Page 2 of 2



Fiig:

A542a0