NSN 4720-00-859-9907

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-859-9907

Cross Sectional Shape:
Round
Thread Class:
2b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
1.000 inches
Tempurature Rating:
-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response
Outside Diameter:
1.410 inches
Minimum Inside Bending Radius:
12.000 inches
Exterior Color:
Black
Connection Style:
Swivel nut flare 1st end
End Connection Design:
Straight 2nd end
Connection Type:
Threaded internal tube 1st end
Features Provided:
Nonskive and reusable end fittings
Burst Test Pressure:
4000.0 pounds per square inch
Layer Composition And Location:
1st layer braided steel wire and outer layer molded rubber, synthetic
Maximum Operating Pressure:
1000.0 pounds per square inch
Thread Size:
0.750 inches 2nd end
Seat Angle:
37.0 degrees 1st end
Hydrostatic Test Pressure:
2000.0 pounds per square inch
Flow Angle:
90.0 degrees 1st end
Outer Covering Environmental Protection:
Abrasion resistant and oil resistant and weatherproof

Inside Surface Condition:

Smooth

NSN 4720-00-859-9907

Nonmetallic Hose Assembly - Page 2 of 2



Measuring Method And Length:
25.500 inches
Media For Which Designed:
Fuel/oil, hydrocarbon single response
Thread Series Designator:
Unf 1st end
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A542a0