Nonmetallic Hose Assembly - Page 1 of 2



synthetic

View Online at https://aerobasegroup.com/nsn/4720-00-859-9914

Cross Sectional Shape:	
Round	
Thread Direction:	
Right-hand 1st end	
Inside Diameter:	
1.000 inches	
Tempurature Rating:	
-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response	
Outside Diameter:	
1.625 inches	
Minimum Inside Bending Radius:	
6.000 inches	
Connection Style:	
Plain 1st end	
End Connection Design:	
Straight 1st end	
Connection Type:	
Threaded external pipe 1st end	
Burst Test Pressure:	
1000.0 pounds per square inch	
Layer Composition And Location:	
1st layer braided textile yarn and 2nd layer braided textile yarn and 3rd layer braided wire an	d outer layer molded rubber,
Maximum Operating Pressure:	
250.0 pounds per square inch	
Thread Size:	
1.000 inches 1st end	
Hydrostatic Test Pressure:	
500.0 pounds per square inch	
Outer Covering Environmental Protection:	
Mildew resistant and oil resistant	
Inside Surface Condition:	
Smooth	
Measuring Method And Length:	
19.500 inches	
Media For Which Designed:	
Fuel/oil, hydrocarbon single response	
Thread Series Designator:	
Npt 1st end	
Shelf Life:	
N/a	
Unit Of Measure:	

Nonmetallic Hose Assembly - Page 2 of 2

Demilitarization:

No

Fiig:

A542a0

