## NSN 4720-00-860-9492

**Cross Sectional Shape:** 

Round

Thread Class: 3b 2nd end

Thread Direction:
Right-hand 2nd end
Inside Diameter:
0.188 inches

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-860-9492

Tempurature Rating:
-65.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response
Outside Diameter:
0.312 inches
Minimum Inside Bending Radius:
2.000 inches
Connection Style:
Swivel nut flare 2nd end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 2nd end
Features Provided:
Electrostatic discharge capability
Burst Test Pressure:
12000.0 pounds per square inch
Layer Composition And Location:
Outer layer braided corrosion resistant steel wire
Maximum Operating Pressure:
1500.0 pounds per square inch
1000.0 pourtus per square mon
Thread Size:
Thread Size:
Thread Size: 0.438 inches 2nd end
Thread Size:  0.438 inches 2nd end  Seat Angle:
Thread Size:  0.438 inches 2nd end  Seat Angle:  37.0 degrees 2nd end
Thread Size:  0.438 inches 2nd end  Seat Angle:  37.0 degrees 2nd end  Hydrostatic Test Pressure:
Thread Size:  0.438 inches 2nd end  Seat Angle:  37.0 degrees 2nd end  Hydrostatic Test Pressure:  3000.0 pounds per square inch
Thread Size:  0.438 inches 2nd end  Seat Angle:  37.0 degrees 2nd end  Hydrostatic Test Pressure:  3000.0 pounds per square inch  Flow Angle:
Thread Size:  0.438 inches 2nd end  Seat Angle:  37.0 degrees 2nd end  Hydrostatic Test Pressure:  3000.0 pounds per square inch  Flow Angle:  90.0 degrees 2nd end
Thread Size:  0.438 inches 2nd end  Seat Angle:  37.0 degrees 2nd end  Hydrostatic Test Pressure:  3000.0 pounds per square inch  Flow Angle:  90.0 degrees 2nd end  Outer Covering Environmental Protection:
Thread Size:  0.438 inches 2nd end  Seat Angle:  37.0 degrees 2nd end  Hydrostatic Test Pressure:  3000.0 pounds per square inch  Flow Angle:  90.0 degrees 2nd end  Outer Covering Environmental Protection:  Corrosion resistant
Thread Size:  0.438 inches 2nd end  Seat Angle:  37.0 degrees 2nd end  Hydrostatic Test Pressure:  3000.0 pounds per square inch  Flow Angle:  90.0 degrees 2nd end  Outer Covering Environmental Protection:  Corrosion resistant  Vacuum In Torr:
Thread Size:  0.438 inches 2nd end  Seat Angle:  37.0 degrees 2nd end  Hydrostatic Test Pressure:  3000.0 pounds per square inch  Flow Angle:  90.0 degrees 2nd end  Outer Covering Environmental Protection:  Corrosion resistant  Vacuum In Torr:  50.8
Thread Size:  0.438 inches 2nd end  Seat Angle:  37.0 degrees 2nd end  Hydrostatic Test Pressure:  3000.0 pounds per square inch  Flow Angle:  90.0 degrees 2nd end  Outer Covering Environmental Protection:  Corrosion resistant  Vacuum In Torr:  50.8  Inside Surface Condition:

## NSN 4720-00-860-9492

Nonmetallic Hose Assembly - Page 2 of 2



modeaning modera / and zongan	Measuring	Method	And	Length:
-------------------------------	-----------	--------	-----	---------

17.625 inches working

**Thread Series Designator:** 

Unjf 2nd end

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A542a0