

View Online at <https://aerobasegroup.com/nsn/4720-00-860-9839>

Cross Sectional Shape:

Round

Thread Class:

3a 2nd end

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.125 inches

Temperature Rating:

-67.0 degrees fahrenheit single response and 200.0 degrees fahrenheit single response

Outside Diameter:

0.469 inches

Hose Or Tubing Specification/std Data:

Sae j1401-81343 standard (includes industry or association standards, individual manufactureer standards, etc.).

End Connection Design:

Straight 2nd end

End Fitting Component And Material:

Complete fitting steel all ends

Fitting Component And Surface Treatment:

Complete fitting cadmium 1st end

Connection Type:

Threaded internal tube 1st end

Thready Qty Per Inch (tpi):

24 1st end

Second End Relationship With First End:

Not identical

Burst Test Pressure:

5000.0 pounds per square inch

First End Swivel Action Capability:

Not included

Layer Composition And Location:

1st layer rubber impregnated braided cotton cord err-100 or 2nd layer rubber impregnated braided rayon cord err-100 or 2nd layer rubber impregnated cotton fabric err-100

Maximum Operating Pressure:

1500.0 pounds per square inch

Thread Size:

0.438 inches 1st end

Seat Angle:

42.0 degrees 1st end

Outer Covering Environmental Protection:

Cold resistant and ozone resistant and salt water resistant and weatherproof

Inside Surface Condition:

Smooth

Measuring Method And Length:

16.500 inches working

Second End Swivel Action Capability:

Not included

Special Features:

Inner conveying tube material-rubber, synthetic

Media For Which Designed:

Brake fluid, nonmineral oil single response

Thread Series Designator:

Uns 1st end

Specification Data:

Sae j1401-81343 national std/spec

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0