

View Online at <https://aerobasegroup.com/nsn/4720-00-862-3665>

**Cross Sectional Shape:**

Round

**Thread Class:**

3b 1st end

**Thread Direction:**

Right-hand 1st end

**Inside Diameter:**

0.375 inches

**Temperature Rating:**

-65.0 degrees fahrenheit and 160.0 degrees fahrenheit single response

**Outside Diameter:**

0.594 inches

**Minimum Inside Bending Radius:**

4.000 inches

**Connection Style:**

Swivel nut flare 2nd end

**End Connection Design:**

Straight 1st end

**Connection Type:**

Threaded internal tube 1st end

**Burst Test Pressure:**

1000.0 pounds per square inch

**Layer Composition And Location:**

1st layer braided cotton cord and outer layer molded rubber, synthetic

**Maximum Operating Pressure:**

150.0 pounds per square inch

**Thread Size:**

0.562 inches 2nd end

**Seat Angle:**

37.0 degrees 2nd end

**Hydrostatic Test Pressure:**

300.0 pounds per square inch

**Flow Angle:**

45.0 degrees 2nd end

**Inside Surface Condition:**

Smooth

**Measuring Method And Length:**

14.750 inches working

**Media For Which Designed:**

Fuel/oil, hydrocarbon single response

**Thread Series Designator:**

Unf 2nd end

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A542a0