NSN 4720-00-865-2127

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-865-2127

Cross Sectional Shape:
Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.219 inches
Tempurature Rating:
-65.0 degrees fahrenheit and 275.0 degrees fahrenheit single response
Outside Diameter:
0.484 inches
Minimum Inside Bending Radius:
3.000 inches
Connection Style:
Swivel nut flare 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Features Provided:
Electrostatic discharge capability
Burst Test Pressure:
16000.0 pounds per square inch
Layer Composition And Location:
1st layer braided corrosion resistant steel wire and outer layer braided corrosion resistant steel wire
1st layer braided corrosion resistant steel wire and outer layer braided corrosion resistant steel wire Maximum Operating Pressure:
Maximum Operating Pressure:
Maximum Operating Pressure: 3000.0 pounds per square inch
Maximum Operating Pressure: 3000.0 pounds per square inch Thread Size:
Maximum Operating Pressure: 3000.0 pounds per square inch Thread Size: 0.438 inches 1st end
Maximum Operating Pressure: 3000.0 pounds per square inch Thread Size: 0.438 inches 1st end Seat Angle:
Maximum Operating Pressure: 3000.0 pounds per square inch Thread Size: 0.438 inches 1st end Seat Angle: 37.0 degrees 1st end
Maximum Operating Pressure: 3000.0 pounds per square inch Thread Size: 0.438 inches 1st end Seat Angle: 37.0 degrees 1st end Hydrostatic Test Pressure:
Maximum Operating Pressure: 3000.0 pounds per square inch Thread Size: 0.438 inches 1st end Seat Angle: 37.0 degrees 1st end Hydrostatic Test Pressure: 6000.0 pounds per square inch
Maximum Operating Pressure: 3000.0 pounds per square inch Thread Size: 0.438 inches 1st end Seat Angle: 37.0 degrees 1st end Hydrostatic Test Pressure: 6000.0 pounds per square inch Inside Surface Condition:
Maximum Operating Pressure: 3000.0 pounds per square inch Thread Size: 0.438 inches 1st end Seat Angle: 37.0 degrees 1st end Hydrostatic Test Pressure: 6000.0 pounds per square inch Inside Surface Condition: Smooth
Maximum Operating Pressure: 3000.0 pounds per square inch Thread Size: 0.438 inches 1st end Seat Angle: 37.0 degrees 1st end Hydrostatic Test Pressure: 6000.0 pounds per square inch Inside Surface Condition: Smooth Measuring Method And Length:

Unf 1st end

Thread Series Designator:

NSN 4720-00-865-2127

Nonmetallic Hose Assembly - Page 2 of 2



_			•		
•	n	ο.	•	18	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0