## NSN 4720-00-865-3508

Nonmetallic Hose Assembly - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/4720-00-865-3508 **Cross Sectional Shape:** Round **Thread Class:** 

3b 1st end

**Thread Direction:** 

Right-hand 1st end

**Inside Diameter:** 

0.212 inches

**Tempurature Rating:** 

-65.0 degrees fahrenheit single response and 400.0 degrees fahrenheit single response

**Outside Diameter:** 

Between 0.360 inches and 0.390 inches

**Minimum Inside Bending Radius:** 

1.500 inches

**Connection Style:** 

Swivel nut flare 1st end

**End Connection Design:** 

Straight 1st end

**Connection Type:** 

Threaded internal tube 1st end

**Burst Test Pressure:** 

16000.0 pounds per square inch

**Layer Composition And Location:** 

Outer layer braided corrosion resistant steel wire

**Maximum Operating Pressure:** 

3000.0 pounds per square inch

**Thread Size:** 

0.438 inches 1st end

Seat Angle:

37.0 degrees 1st end

**Hydrostatic Test Pressure:** 

6000.0 pounds per square inch

**Inside Surface Condition:** 

Smooth

**Measuring Method And Length:** 

8.375 inches working

**Thread Series Designator:** 

Unjf 1st end

**Specification Data:** 

81343-as153 professional/industrial association standard

Shelf Life:

N/a

## NSN 4720-00-865-3508

Nonmetallic Hose Assembly - Page 2 of 2



	• •				
In	18	<i>(</i> )+	МА	261	ıre:

--

Demilitarization:

No

Fiig:

A542a0