Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-865-3927

Cross Sectional Shape:	
Round	
hread Class:	
b 1st end	
Thread Direction:	
Right-hand 1st end	
nside Diameter:	
.406 inches	
empurature Rating:	
65.0 degrees fahrenheit and 160.0 degrees fahrenheit single response	
Dutside Diameter:	
.766 inches	
Connection Style:	
Swivel nut flare 1st end	
Ind Connection Design:	
Straight 1st end	
Connection Type:	
hreaded internal tube 1st end	
hready Qty Per Inch (tpi):	
6 1st end	
Burst Test Pressure:	
000.0 pounds per square inch	
ayer Composition And Location:	
st layer braided cotton cord and 2nd layer braided steel wire and outer layer molded rubb	er, synthetic
Iaximum Operating Pressure:	
000.0 pounds per square inch	
hread Size:	
.750 inches 1st end	
Seat Angle:	
5.0 degrees 1st end	
lydrostatic Test Pressure:	
000.0 pounds per square inch	
Duter Covering Environmental Protection:	
ire retardant and hydraulic solution resistant and mildew resistant and oil resistant	
nside Surface Condition:	
Smooth	
leasuring Method And Length:	
1.500 inches	
ledia For Which Designed:	
uel/oil, hydrocarbon single response	
hread Series Designator:	
Jnjf 1st end	

NSN 4720-00-865-3927

Nonmetallic Hose Assembly - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0

