## NSN 4720-00-865-6765

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-865-6765

Cross Sectional Shape:
Round
Thread Class:
3b 2nd end
Thread Direction:
Right-hand 2nd end
Inside Diameter:
0.219 inches
Tempurature Rating:
-65.0 degrees fahrenheit and 275.0 degrees fahrenheit single response
Outside Diameter:
0.484 inches
Minimum Inside Bending Radius:
3.000 inches
Exterior Color:
Natural
Connection Style:
Swivel nut flare 2nd end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 2nd end
Features Provided:
Electrostatic discharge capability
Burst Test Pressure:
16000.0 pounds per square inch
Layer Composition And Location:
1st layer braided corrosion resistant steel wire and outer layer braided corrosion resistant steel wire
Maximum Operating Pressure:
3000.0 pounds per square inch
Thread Size:
0.438 inches 2nd end
Seat Angle:
37.0 degrees 2nd end
Hydrostatic Test Pressure:
6000.0 pounds per square inch
Flow Angle:
45.0 degrees 2nd end
Outer Covering Environmental Protection:
Corrosion resistant
Inside Surface Condition:

Smooth

## NSN 4720-00-865-6765

Nonmetallic Hose Assembly - Page 2 of 2



Measuring	Method	And	Length:

13.250 inches working

**Thread Series Designator:** 

Unf 2nd end

Shelf Life:

N/a

**Unit Of Measure:** 

Demilitarization:

No

Fiig:

A542a0