Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-866-5139

Cross Sectional Shape:
Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.625 inches
Tempurature Rating:
-40.0 degrees fahrenheit single response and 200.0 degrees fahrenheit single response
Outside Diameter:
0.910 inches
Minimum Inside Bending Radius:
6.000 inches
Exterior Color:
Black
Connection Style:
Swivel nut flare 1st end
End Connection Design:
Straight 1st end
End Fitting Component And Material:
Complete fitting copper alloy all ends
Connection Type:
Threaded internal tube 1st end
Thready Qty Per Inch (tpi):
10 1st end
Burst Test Pressure:
10000.0 pounds per square inch
First End Swivel Action Capability:
Not included
Layer Composition And Location:
1st layer braided textile yarn err-100
Maximum Operating Pressure:
250.0 pounds per square inch
Thread Size:
0.625 inches 1st end
Seat Angle:
37.0 degrees 1st end
Hydrostatic Test Pressure:
500.0 pounds per square inch
Outer Covering Environmental Protection:
Oil resistant and ozone resistant

Nonmetallic Hose Assembly - Page 2 of 2



Inside Surface Condition:

Smooth

Measuring Method And Length:

100.000 inches

Special Features:

Inner conveying tube material-rubber, synthetic

Media For Which Designed:

Air single response and ethylene glycol single response and oil, lubricating, diester base single response

Thread Series Designator:

Uns 1st end

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A542a0