Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-866-6409

C	cross Sectional Shape:
F	Cound
т	hread Class:
3	b 1st end
Т	hread Direction:
F	light-hand 1st end
h	nside Diameter:
0	.406 inches
Т	empurature Rating:
-(	65.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response
C	Dutside Diameter:
0	.562 inches
N	linimum Inside Bending Radius:
4	.625 inches
A	ngle Between Rigid Elbow Fittings In Deg:
0	.0
C	connection Style:
S	wivel nut flare 1st end
E	nd Connection Design:
E	lbow 1st end
C	Connection Type:
Т	hreaded internal tube 1st end
Т	hready Qty Per Inch (tpi):
1	6 1st end
B	Burst Test Pressure:
8	000.0 pounds per square inch
L	ayer Composition And Location:
C	Outer layer braided corrosion resistant steel wire
N	laximum Operating Pressure:
1	500.0 pounds per square inch
Т	hread Size:
0	.750 inches 1st end
S	eat Angle:
3	7.0 degrees 1st end
F	lydrostatic Test Pressure:
3	000.0 pounds per square inch
F	low Angle:
9	0.0 degrees 1st end
۷	acuum In Torr:
5	0.8
h	nside Surface Condition:
S	Smooth



Measuring Method And Length: 90.500 inches working Media For Which Designed: Fuel/oil, hydrocarbon single response Thread Series Designator: Unf 1st end Shelf Life: N/a Unit Of Measure: --Demilitarization: No Fiig: A542a0