

View Online at <https://aerobasegroup.com/nsn/4720-00-866-7919>

Cross Sectional Shape:

Round

Thread Class:

3b 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

Between 0.851 inches and 0.906 inches

Temperature Rating:

-65.0 degrees fahrenheit and 450.0 degrees fahrenheit single response

Outside Diameter:

Between 1.078 inches and 1.140 inches

Recess Diameter:

0.844 inches 2nd end

Recess Depth:

0.030 inches 2nd end

Minimum Inside Bending Radius:

7.400 inches

Exterior Color:

Natural

Center To Center Distance Between Bolt Holes Along Width:

1.312 inches 2nd end

Center To Center Distance Between Bolt Holes Along Length:

1.312 inches 2nd end

Bolt Hole Quantity:

4 1st end

Flange Length:

1.750 inches 2nd end

Flange Width:

1.750 inches 2nd end

Connection Style:

Swivel nut flare 1st end

Bolt Hole Diameter:

0.205 inches 2nd end

End Flange Construction:

Solid 2nd end

End Connection Design:

Straight 2nd end

Connection Type:

Threaded internal tube 1st end

Features Provided:

Electrostatic discharge capability

Thready Qty Per Inch (tpi):

12 1st end

Burst Test Pressure:

1200.0 pounds per square inch

Layer Composition And Location:

1st layer braided corrosion resistant steel wire and outer layer braided corrosion resistant steel wire

Maximum Operating Pressure:

200.0 pounds per square inch

Thread Size:

1.312 inches 1st end

Seat Angle:

37.0 degrees 1st end

Hydrostatic Test Pressure:

600.0 pounds per square inch

Flow Angle:

90.0 degrees 1st end

Inside Surface Condition:

Smooth

Measuring Method And Length:

35.700 inches working and 36.200 inches working

Flange Style:

Rectangular (includes square) 2nd end

Media For Which Designed:

Fuel/oil, hydrocarbon single response

Thread Series Designator:

Unf 1st end

Fsc Application Data:

Oil system, aircraft

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0