NSN 4720-00-866-7923

Cross Sectional Shape:

Inside Diameter: 0.937 inches

Tempurature Rating:

Round

Metallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-866-7923

-40.0 degrees fahrenheit single response and 200.0 degrees fahrenheit single response

| Flange Inickness: |
|--|
| 0.156 inches 2nd end |
| Outside Diameter: |
| 1.400 inches |
| Inner Conveying Tube Style: |
| Annular open-pitch corrugated |
| Exterior Color: |
| Natural |
| Center To Center Distance Between Bolt Holes Along Width: |
| 1.134 inches 2nd end |
| Center To Center Distance Between Bolt Holes Along Length: |
| 1.619 inches 2nd end |
| Bolt Hole Quantity: |
| 4 2nd end |
| Flange Length: |
| 2.324 inches 2nd end |
| Flange Width: |
| 1.775 inches 2nd end |
| Connection Style: |
| Raised 2nd end |
| Bolt Hole Diameter: |
| 0.305 inches 2nd end |
| Raised Face Height: |
| 0.545 inches 2nd end |
| Raised Face Diameter: |
| 1.246 inches 2nd end |
| End Flange Construction: |
| Solid 2nd end |
| End Connection Design: |
| Straight 1st end |
| Connection Type: |
| Unthreaded external tube 1st end |
| Burst Test Pressure: |
| 500.0 pounds per square inch |
| Layer Composition And Location: |
| Outer layer braided corrosion resistant steel wire |

NSN 4720-00-866-7923Metallic Hose Assembly - Page 2 of 2



| Maximum Operating Pressure: |
|--|
| 75.0 pounds per square inch |
| Hydrostatic Test Pressure: |
| 150.0 pounds per square inch |
| Flow Angle: |
| 64.5 degrees 2nd end |
| Outer Covering Environmental Protection: |
| Corrosion resistant |
| Measuring Method And Length: |
| 10.000 inches |
| Flange Style: |
| Rectangular (includes square) 2nd end |
| Outside Diameter Tube Accommodated: |
| 1.005 inches 1st end |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A542a0 |