

View Online at <https://aerobasegroup.com/nsn/4720-00-866-7923>

Cross Sectional Shape:

Round

Inside Diameter:

0.937 inches

Temperature Rating:

-40.0 degrees fahrenheit single response and 200.0 degrees fahrenheit single response

Flange Thickness:

0.156 inches 2nd end

Outside Diameter:

1.400 inches

Inner Conveying Tube Style:

Annular open-pitch corrugated

Exterior Color:

Natural

Center To Center Distance Between Bolt Holes Along Width:

1.134 inches 2nd end

Center To Center Distance Between Bolt Holes Along Length:

1.619 inches 2nd end

Bolt Hole Quantity:

4 2nd end

Flange Length:

2.324 inches 2nd end

Flange Width:

1.775 inches 2nd end

Connection Style:

Raised 2nd end

Bolt Hole Diameter:

0.305 inches 2nd end

Raised Face Height:

0.545 inches 2nd end

Raised Face Diameter:

1.246 inches 2nd end

End Flange Construction:

Solid 2nd end

End Connection Design:

Straight 1st end

Connection Type:

Unthreaded external tube 1st end

Burst Test Pressure:

500.0 pounds per square inch

Layer Composition And Location:

Outer layer braided corrosion resistant steel wire

Maximum Operating Pressure:

75.0 pounds per square inch

Hydrostatic Test Pressure:

150.0 pounds per square inch

Flow Angle:

64.5 degrees 2nd end

Outer Covering Environmental Protection:

Corrosion resistant

Measuring Method And Length:

10.000 inches

Flange Style:

Rectangular (includes square) 2nd end

Outside Diameter Tube Accommodated:

1.005 inches 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A542a0