NSN 4720-00-870-5125

Abrasion resistant and corrosion resistant

Cross Sectional Shape:

Round

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-870-5125

Thread Class:
3b 2nd end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.313 inches
Tempurature Rating:
-65.0 degrees fahrenheit single response and 250.0 degrees fahrenheit single response
Outside Diameter:
0.562 inches
Minimum Inside Bending Radius:
4.625 inches
Exterior Color:
Natural
Angle Between Rigid Elbow Fittings In Deg:
113.0
Connection Style:
Swivel nut flare 2nd end
End Connection Design:
Elbow 2nd end
Connection Type:
Threaded internal tube 1st end
Features Provided:
Electrostatic discharge capability
Burst Test Pressure:
1800.0 pounds per square inch
Layer Composition And Location:
Outer layer braided corrosion resistant steel wire
Maximum Operating Pressure:
450.0 pounds per square inch
Thread Size:
0.562 inches 2nd end
Seat Angle:
37.0 degrees 2nd end
Hydrostatic Test Pressure:
900.0 pounds per square inch
Flow Angle:
90.0 degrees 2nd end
Outer Covering Environmental Protection:

NSN 4720-00-870-5125

Nonmetallic Hose Assembly - Page 2 of 2



Vacuum In Torr:
50.8
Inside Surface Condition:
Smooth
Measuring Method And Length:
16.680 inches working and 16.920 inches working
Special Features:
End fittings must be permanently attaached
Thread Series Designator:
Unf 2nd end
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A542a0