
Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-870-6295

| Cross Sectional Shape: |
|---|
| Round |
| Thread Class: |
| 2b 1st end |
| Thread Direction: |
| Right-hand 1st end |
| Inside Diameter: |
| 0.500 inches |
| Tempurature Rating: |
| -40.0 degrees fahrenheit single response and 200.0 degrees fahrenheit single response |
| Outside Diameter: |
| 0.750 inches |
| Minimum Inside Bending Radius: |
| 5.000 inches |
| Connection Style: |
| Swivel nut flare 1st end |
| End Connection Design: |
| Straight 1st end |
| Connection Type: |
| Threaded internal tube 1st end |
| Burst Test Pressure: |
| 1000.0 pounds per square inch |
| Maximum Operating Pressure: |
| 250.0 pounds per square inch |
| Thread Size: |
| 0.750 inches 1st end |
| Seat Angle: |
| 37.0 degrees 1st end and 45.0 degrees 1st end |
| Outer Covering Environmental Protection: |
| Oil resistant |
| Inside Surface Condition: |
| Smooth |
| Measuring Method And Length: |
| 32.000 inches excluding end fittings |
| Media For Which Designed: |
| Fuel/oil, hydrocarbon single response |
| Thread Series Designator: |
| Unf 1st end |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |

NSN 4720-00-870-6295

Nonmetallic Hose Assembly - Page 2 of 2

Demilitarization:

No

Fiig:

A542a0

