NSN 4720-00-871-2848

Nonmetallic Hose Assembly - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/4720-00-871-2848 |
|---|
| Cross Sectional Shape: |
| Round |
| Thread Class: |
| 3b 1st end |
| Thread Direction: |
| Right-hand 1st end |
| Inside Diameter: |
| 0.688 inches |
| Tempurature Rating: |
| -40.0 degrees fahrenheit single response and 300.0 degrees fahrenheit single response |
| Outside Diameter: |
| 0.938 inches |
| Minimum Inside Bending Radius: |
| 4.500 inches |
| Connection Style: |
| Swivel nut, flareless 1st end |
| End Connection Design: |
| Straight 1st end |
| Connection Type: |
| Threaded internal tube 1st end |
| Features Provided: |
| Reusable end fittings |
| Thready Qty Per Inch (tpi): |
| 12 1st end |
| Burst Test Pressure: |
| 3750.0 pounds per square inch |
| Layer Composition And Location: |
| Outer layer braided corrosion resistant steel wire |
| Maximum Operating Pressure: |
| 1000.0 pounds per square inch |
| Thread Size: |
| 1.062 inches 1st end |
| Seat Angle: |
| 40.0 de suse e 4 et e a d |

12.0 degrees 1st end

Hydrostatic Test Pressure:

2000.0 pounds per square inch

Outer Covering Environmental Protection:

Fire resistant

Inside Surface Condition:

Smooth

Measuring Method And Length:

15.812 inches working and 16.188 inches working

NSN 4720-00-871-2848

Nonmetallic Hose Assembly - Page 2 of 2



| | Media | For | Which | Design | ned: |
|--|-------|-----|-------|--------|------|
|--|-------|-----|-------|--------|------|

Fuel/oil, hydrocarbon single response

Thread Series Designator:

Unjf 1st end

Specification Data:

96906-ms87029 government standard

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A542a0