NSN 4720-00-871-8258

Cross Sectional Shape:

Thread Direction:
Right-hand 1st end
Inside Diameter:

Round

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-871-8258

0.375 inches					
Tempurature Rating:					
-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response					
Outside Diameter:					
0.781 inches					
Minimum Inside Bending Radius:					
5.000 inches					
Exterior Color:					
Black					
Connection Style:					
Inverted flare 1st end					
End Connection Design:					
Straight 1st end					
Connection Type:					
Threaded external pipe 1st end					
Features Provided:					
Electrostatic discharge capability					
Burst Test Pressure:					
9000.0 pounds per square inch					
Layer Composition And Location:					
1st layer braided steel wire and outer layer molded rubber					
Maximum Operating Pressure:					
2250.0 pounds per square inch					
Thread Size:					
0.375 inches 1st end					
Seat Angle:					
30.0 degrees 1st end					
Hydrostatic Test Pressure:					
4500.0 pounds per square inch					
Outer Covering Environmental Protection:					
Abrasion resistant and oil resistant and weatherproof					
Inside Surface Condition:					
Smooth					
Measuring Method And Length:					
84.000 inches					
Media For Which Designed:					
Fuel/oil, hydrocarbon and hydraulic fluid, water base single response					

NSN 4720-00-871-8258

Nonmetallic Hose Assembly - Page 2 of 2



Th.		Carias	Danie	
1111	reau	Series	Desig	mator.

Nptf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0