## NSN 4720-00-872-3300

**Cross Sectional Shape:** 

N/a

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-872-3300

Round
Thread Class:
2b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.391 inches
Tempurature Rating:
-65.0 degrees fahrenheit single response and 400.0 degrees fahrenheit single response
Outside Diameter:
Between 0.585 inches and 0.615 inches
Minimum Inside Bending Radius:
2.880 inches
Connection Style:
Swivel nut flare 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Burst Test Pressure:
14000.0 pounds per square inch
Layer Composition And Location:
Outer layer braided corrosion resistant steel wire
Maximum Operating Pressure:
3000.0 pounds per square inch
Thread Size:
0.750 inches 1st end
Seat Angle:
37.0 degrees 1st end
Hydrostatic Test Pressure:
6000.0 pounds per square inch
Inside Surface Condition:
Smooth
Measuring Method And Length:
20.000 inches
Thread Series Designator:
Unjf 1st end
Specification Data:
81343-as153 professional/industrial association standard
Shelf Life:

## NSN 4720-00-872-3300

Nonmetallic Hose Assembly - Page 2 of 2



			ure:	

--

Demilitarization:

No

Fiig:

A542a0