NSN 4720-00-872-7698

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-872-7698

Cross Sectional Shape:
Round
Thread Class:
2b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.750 inches
Tempurature Rating:
-40.0 degrees fahrenheit single response and 200.0 degrees fahrenheit single response
Outside Diameter:
1.230 inches
Minimum Inside Bending Radius:
9.500 inches
Exterior Color:
Black
Hose Or Tubing Specification/std Data:
Mil-I-52325, paragraph 3.6.2 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in
specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on
certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
First End Fitting Specification/std Data:
Sae j516, fig.4a or 4b standard (includes industry or association standards, individual manufactureer standards, etc.).
Connection Style:
Swivel nut flare 1st end
End Connection Design:
Straight 1st end
End Fitting Component And Material:
Complete fitting steel all ends
Fitting Component And Surface Treatment:
Complete fitting cadmium and complete fitting zinc 1st end
Connection Type:
Threaded internal tube 1st end
Features Provided:
Reusable end fittings
Thready Qty Per Inch (tpi):
12 1st end
Second End Relationship With First End:
Identical
Burst Test Pressure:
12000.0 pounds per square inch
First End Swivel Action Capability:

Layer Composition And Location:
1st layer spirally laid steel wire err-100

Not included

NSN 4720-00-872-7698

Nonmetallic Hose Assembly - Page 2 of 2



Maximum Operating Pressure:
3000.0 pounds per square inch
Unable To Decode:
Unable to decode or unable to decode
Thread Size:
1.062 inches 1st end
Seat Angle:
37.0 degrees 1st end
Hydrostatic Test Pressure:
6000.0 pounds per square inch
Outer Covering Environmental Protection:
Abrasion resistant and oil resistant and weatherproof
Inside Surface Condition:
Smooth
Measuring Method And Length:
129.000 inches
Special Features:
Aluminum identification sleeve on hose, mil-l-52325, paragraph 3.9.1
Media For Which Designed:
Fuel/oil, hydrocarbon single response
Special Test Features:
Mil-I-52325, paragraph 4.7.2.1
Thread Series Designator:
Un 1st end
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A542a0
Mil-std (military Standard):
Mil-I-52325 spec.