

View Online at <https://aerobasegroup.com/nsn/4720-00-872-7709>

**Cross Sectional Shape:**

Round

**Thread Class:**

2b 1st end

**Thread Direction:**

Right-hand 1st end

**Inside Diameter:**

0.375 inches

**Temperature Rating:**

-25.0 degrees fahrenheit single response and 200.0 degrees fahrenheit single response

**Minimum Inside Bending Radius:**

5.000 inches

**Hose Or Tubing Specification/std Data:**

Mil mil-I-52325, para 3.6.2 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**First End Fitting Specification/std Data:**

Mil mil-I-52325, para 3.6.3 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**End Connection Design:**

Straight 1st end

**End Fitting Component And Material:**

Complete fitting stainless steel and complete fitting steel all ends

**Fitting Component And Surface Treatment:**

Complete fitting cadmium and complete fitting zinc 1st end

**Connection Type:**

Threaded internal tube 1st end

**Second End Relationship With First End:**

Identical

**Burst Test Pressure:**

16000.0 pounds per square inch

**First End Swivel Action Capability:**

Not included

**Layer Composition And Location:**

Outer layer molded rubber err-100

**Unable To Decode:**

Unable to decode or unable to decode

**Maximum Operating Pressure:**

3800.0 pounds per square inch

**Unable To Decode:**

Unable to decode or unable to decode

**Thread Size:**

0.750 inches 1st end

**Seat Angle:**

**Hydrostatic Test Pressure:**

7000.0 pounds per square inch

**Outer Covering Environmental Protection:**

Abrasion resistant and oil resistant and weatherproof

**Inside Surface Condition:**

Smooth

**Measuring Method And Length:**

195.000 inches

**Special Features:**

Aluminum identification sleeve on hose

**Media For Which Designed:**

Hydraulic fluid single response

**Thread Series Designator:**

Unf 1st end

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A542a0