## NSN 4720-00-872-7724

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-872-7724

| Cross Sectional Shape:  |
|---|
| Round   |
| Thread Class:   |
| 2b 1st end  |
| Thread Direction:   |
| Right-hand 1st end  |
| Inside Diameter:  |
| 1.000 inches  |
| Tempurature Rating:   |
| -25.0 degrees fahrenheit and 200.0 degrees fahrenheit single response |
| Outside Diameter:   |
| 1.438 inches  |
| Minimum Inside Bending Radius:  |
| 12.000 inches   |
| Connection Style:   |
| Swivel nut flare 1st end  |
| End Connection Design:  |
| Straight 1st end  |
| Connection Type:  |
| Threaded internal tube 1st end  |
| Thready Qty Per Inch (tpi):   |
| 12 1st end  |
| Burst Test Pressure:  |
| 14000.0 pounds per square inch  |
| Layer Composition And Location:                                       |
| 1st layer braided wire and outer layer molded rubber, synthetic       |
| Maximum Operating Pressure:   |
| 3800.0 pounds per square inch   |
| Thread Size:  |
| 0.937 inches 1st end  |
| Seat Angle:   |
| 37.0 degrees 1st end  |
| Outer Covering Environmental Protection:                              |
| Abrasion resistant and oil resistant and weatherproof                 |
| Measuring Method And Length:  |
| 61.000 inches   |
| Media For Which Designed:   |
| Fuel/oil, hydrocarbon single response                                 |
| Thread Series Designator:   |
| Un 1st end  |
| Shelf Life:   |

N/a

## NSN 4720-00-872-7724

Nonmetallic Hose Assembly - Page 2 of 2



|   | 1  | :. | ~  | 84  |    |    |      |   |
|---|----|----|----|-----|----|----|------|---|
| ι | JN | IT | UΤ | IVI | ea | Sι | ire: | • |

--

Demilitarization:

No

Fiig:

A542a0