

View Online at <https://aerobasegroup.com/nsn/4720-00-873-5048>

Cross Sectional Shape:

Round

Thread Class:

2b 2nd end and 2a 2nd end

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.125 inches

Temperature Rating:

-65.0 degrees fahrenheit single response and 200.0 degrees fahrenheit single response

Outside Diameter:

0.469 inches

Minimum Inside Bending Radius:

3.000 inches

Exterior Color:

Black

Hose Or Tubing Specification/std Data:

Sae j1401 standard (includes industry or association standards, individual manufactureer standards, etc.).

Connection Style:

Inverted flare 2nd end

End Connection Design:

Straight 2nd end

End Fitting Component And Material:

Complete fitting steel all ends

Fitting Component And Surface Treatment:

Complete fitting cadmium 1st end

Connection Type:

Threaded internal and external tube 2nd end

Second End Relationship With First End:

Not identical

Burst Test Pressure:

12000.0 pounds per square inch

First End Swivel Action Capability:

Not included

Layer Composition And Location:

Outer layer molded rubber, synthetic err-100

Maximum Operating Pressure:

3000.0 pounds per square inch

Thread Size:

0.438 inches 1st end

External Protection Type And Location (non-core):

spring guard, round steel coil

Seat Angle:

30.0 degrees 1st end

Hydrostatic Test Pressure:

6000.0 pounds per square inch

Outer Covering Environmental Protection:

Weatherproof

Inside Surface Condition:

Smooth

Measuring Method And Length:

18.219 inches

Second End Swivel Action Capability:

Not included

Seat Radius:

0.016 inches 2nd end

Special Features:

External protection type and location- spring guard, round steel coil , inner conveying tube material-rubber, synthetic

Media For Which Designed:

Brake fluid, nonmineral oil single response

Thread Series Designator:

Unf 2nd end and unf 2nd end

Specification Data:

Sae j1401 national std/spec

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0