

View Online at <https://aerobasegroup.com/nsn/4720-00-875-9873>

Cross Sectional Shape:

Round

Thread Class:

3b 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

Between 0.406 inches and 0.437 inches

Temperature Rating:

-65.0 degrees fahrenheit and 200.0 degrees fahrenheit single response

Outside Diameter:

Between 0.740 inches and 0.800 inches

Minimum Inside Bending Radius:

4.625 inches

Angle Between Rigid Elbow Fittings In Deg:

180.0

Connection Style:

Swivel nut, flareless 1st end

End Connection Design:

Elbow 1st end

Connection Type:

Threaded internal tube 1st end

Burst Test Pressure:

8000.0 pounds per square inch

Layer Composition And Location:

1st layer braided cotton cord and 2nd layer braided steel wire and outer layer rubber impregnated braided cotton cord

Maximum Operating Pressure:

2000.0 pounds per square inch

Thread Size:

0.750 inches 1st end

Seat Angle:

45.0 degrees 1st end

Hydrostatic Test Pressure:

4000.0 pounds per square inch

Flow Angle:

90.0 degrees 1st end

Outer Covering Environmental Protection:

Alcohol resistant and fuel resistant and hydraulic solution resistant and mildew resistant

Inside Surface Condition:

Smooth

Measuring Method And Length:

29.750 inches working and 30.250 inches working

Media For Which Designed:

Ethylene glycol single response

Thread Series Designator:

Unf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0