

View Online at <https://aerobasegroup.com/nsn/4720-00-876-3498>

**Cross Sectional Shape:**

Round

**Thread Class:**

3b 1st end

**Thread Direction:**

Right-hand 1st end

**Inside Diameter:**

1.375 inches

**Temperature Rating:**

-40.0 degrees fahrenheit and 300.0 degrees fahrenheit single response

**Flange Thickness:**

0.300 inches 2nd end

**Outside Diameter:**

1.704 inches

**Minimum Inside Bending Radius:**

9.000 inches

**Exterior Color:**

Natural

**Center To Center Distance Between Bolt Holes Along Width:**

1.810 inches 2nd end

**Center To Center Distance Between Bolt Holes Along Length:**

1.810 inches 2nd end

**Bolt Hole Quantity:**

4 2nd end

**Flange Length:**

2.380 inches 2nd end

**Flange Width:**

2.380 inches 2nd end

**Connection Style:**

Swivel nut flare 1st end

**Bolt Hole Diameter:**

0.266 inches 2nd end

**Raised Face Height:**

0.015 inches 2nd end

**Raised Face Diameter:**

2.120 inches 2nd end

**End Flange Construction:**

Solid 2nd end

**End Connection Design:**

Straight 2nd end

**Connection Type:**

Threaded internal tube 1st end

**Features Provided:**

Internal support

**Thready Qty Per Inch (tpi):**

12 1st end

**Burst Test Pressure:**

2000.0 pounds per square inch

**Layer Composition And Location:**

1st layer braided corrosion resistant steel wire, partial coverage and outer layer braided corrosion resistant steel wire

**Maximum Operating Pressure:**

250.0 pounds per square inch

**Thread Size:**

1.875 inches 1st end

**Seat Angle:**

37.0 degrees 1st end

**Hydrostatic Test Pressure:**

800.0 pounds per square inch

**Flow Angle:**

90.0 degrees 1st end

**Outer Covering Environmental Protection:**

Corrosion resistant

**Inside Surface Condition:**

Smooth

**Measuring Method And Length:**

17.250 inches working

**Flange Style:**

Rectangular (includes square) 2nd end

**Special Features:**

Flat spirally wound corrosion resistant steel internal support

**Media For Which Designed:**

Fuel/oil, hydrocarbon single response

**Supplementary Features:**

This item has been reviewed for asbestos material. The current approved source, 32142, has indicated their part number contained asbestos prior to 1984. They continue to manufacture the same part number without asbestos material after 1984

**Thread Series Designator:**

Un 1st end

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A542a0