Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-876-8825

Round	
Thread Direction:	
Right-hand 1st end	
nside Diameter:	
1.000 inches	
Tempurature Rating:	
40.0 degrees fahrenheit and 200	0 degrees fahrenheit single response
Outside Diameter:	
1.500 inches	
Minimum Inside Bending Radius	
11.000 inches	
Connection Style:	
nverted flare 1st end	
End Connection Design:	
Straight 1st end	
Connection Type:	
Threaded external pipe 1st end	
Thready Qty Per Inch (tpi):	
11-1/2 1st end	
Burst Test Pressure:	
7500.0 pounds per square inch	
Layer Composition And Locatio	n:
1st layer braided steel wire and 2	nd layer sheet rubber and 3rd layer braided steel wire and 4th layer sheet rubber and 5th layer braided
iber and outer layer molded rubb	r
Maximum Operating Pressure:	
1875.0 pounds per square inch	
Thread Size:	
1.000 inches 1st end	
Seat Angle:	
30.0 degrees 1st end	
Hydrostatic Test Pressure:	
3750.0 pounds per square inch	
Inside Surface Condition:	
Smooth	
Measuring Method And Length:	
91.000 inches	
Media For Which Designed:	
Fuel/oil, hydrocarbon single respo	nse
Thread Series Designator:	
Nptf 1st end	
Shelf Life:	
N/a	

## NSN 4720-00-876-8825

Nonmetallic Hose Assembly - Page 2 of 2



Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0