## NSN 4720-00-877-5167

**Cross Sectional Shape:** 

Round

Thread Class: 3b 1st end

**Thread Direction:** 

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-877-5167

| Right-hand 1st end  |
|---|
| Inside Diameter:  |
| 0.219 inches  |
| Tempurature Rating:   |
| -65.0 degrees fahrenheit single response and 400.0 degrees fahrenheit single response |
| Outside Diameter:   |
| Between 0.453 inches and 0.469 inches   |
| Minimum Inside Bending Radius:  |
| 3.000 inches  |
| Exterior Color:   |
| Natural or silver   |
| Connection Style:   |
| Swivel nut flare 1st end  |
| End Connection Design:  |
| Straight 1st end  |
| Connection Type:  |
| Threaded internal tube 1st end  |
| Burst Test Pressure:  |
| 16000.0 pounds per square inch  |
| Layer Composition And Location:   |
| Outer layer braided corrosion resistant steel wire                                    |
| Maximum Operating Pressure:   |
| 3000.0 pounds per square inch   |
| Thread Size:  |
| 0.438 inches 1st end  |
| Seat Angle:   |
| 37.0 degrees 1st end  |
| Hydrostatic Test Pressure:  |
| 6000.0 pounds per square inch   |
| Outer Covering Environmental Protection:  |
| Corrosion resistant   |
| Inside Surface Condition:   |
| Smooth  |
| Measuring Method And Length:  |
| 15.312 inches   |
| Thread Series Designator:   |
| Unf 1st end   |

## NSN 4720-00-877-5167

Nonmetallic Hose Assembly - Page 2 of 2



| _ |    |      |   |        |  |
|---|----|------|---|--------|--|
| c | hο | JIF. |   | .ife:  |  |
| J |    |      | _ | .II C. |  |

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A542a0