Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-877-5169

_	
	Sectional Shape:
Round	
	I Class:
3b 1st e	end
Thread	I Direction:
Right-h	and 1st end
Inside	Diameter:
0.313 ir	nches
Tempu	Irature Rating:
-65.0 d	egrees fahrenheit single response and 400.0 degrees fahrenheit single response
Outsid	e Diameter:
0.563 ir	nches
Minimu	um Inside Bending Radius:
5.000 ir	nches
Conne	ction Style:
Swivel	nut flare 1st end
End Co	onnection Design:
Straigh	t 1st end
Conne	ction Type:
Thread	led internal tube 1st end
Burst 1	Test Pressure:
12000.	0 pounds per square inch
Layer (Composition And Location:
Outer la	ayer braided corrosion resistant steel wire
Maxim	um Operating Pressure:
3000.0	pounds per square inch
Thread	l Size:
0.562 iı	nches 1st end
Seat A	ngle:
37.0 de	egrees 1st end
Hydros	static Test Pressure:
6000.0	pounds per square inch
Outer (Covering Environmental Protection:
Corrosi	ion resistant
Inside	Surface Condition:
Smooth	ı
Measu	ring Method And Length:
33.000	inches working
Thread	I Series Designator:
Unf 1st	
Shelf L	life:
N/a	

NSN 4720-00-877-5169

Nonmetallic Hose Assembly - Page 2 of 2



Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0