

View Online at <https://aerobasegroup.com/nsn/4720-00-878-0700>

Cross Sectional Shape:

Round

Inside Diameter:

0.844 inches

Bolt Circle Diameter:

3.125 inches 1st end

Flange Thickness:

0.562 inches 1st end

Outside Diameter:

1.149 inches

Exterior Color:

Natural

First End Fitting Specification/std Data:

Usasi b16-5 standard (includes industry or association standards, individual manufactureer standards, etc.).

Bolt Hole Quantity:

4 2nd end

Flange Outside Diameter:

4.250 inches 1st end

Connection Style:

Raised swivel 1st end

Bolt Hole Diameter:

0.625 inches 1st end

Raised Face Height:

0.062 inches 1st end

Raised Face Diameter:

2.000 inches 1st end

End Flange Construction:

Solid 1st end

End Connection Design:

Straight 1st end

End Fitting Component And Material:

Nipple steel comp 304 1st end

Connection Type:

Raised face flange 1st end

Features Provided:

Electrostatic discharge capability

Second End Relationship With First End:

Identical

First End Swivel Action Capability:

Not included

Layer Composition And Location:

Outer layer braided corrosion resistant steel wire

Maximum Operating Pressure:

150.0 pounds per square inch

Hydrostatic Test Pressure:

225.0 pounds per square inch

Vacuum In Torr:

25.4

Inside Surface Condition:

Smooth

Measuring Method And Length:

17.500 inches working

Flange Style:

Round w/ bolt holes 1st end

Special Features:

Pac aagq is the leg length, assembly includes a 90 degree stainless steel elbow in center of hose

Media For Which Designed:

Air single response and steam single response

Specification Data:

Usasi b16-5 national std/spec

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0