## NSN 4720-00-878-4701

**Cross Sectional Shape:** 

Round

Thread Class: 3b 1st end

Thread Direction:
Right-hand 1st end
Inside Diameter:
0.125 inches

**Tempurature Rating:** 

**Outside Diameter:** 

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-878-4701

-65.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response

0.250 inches
Connection Style:
Swivel nut flare 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Features Provided:
Electrostatic discharge capability
Burst Test Pressure:
7500.0 pounds per square inch
Layer Composition And Location:
Outer layer braided corrosion resistant steel wire
Maximum Operating Pressure:
1500.0 pounds per square inch
Thread Size:
0.375 inches 1st end
Seat Angle:
37.0 degrees 1st end
Hydrostatic Test Pressure:
3000.0 pounds per square inch
Inside Surface Condition:
Smooth
Measuring Method And Length:
12.000 inches working
Special Features:
In accordance w/aso standard dwg aso to586
Thread Series Designator:
Unf 1st end
Specification Data:
81349-mil-h-25579 government specification

## NSN 4720-00-878-4701

Nonmetallic Hose Assembly - Page 2 of 2



Specification	Or	Standard:
---------------	----	-----------

3 size

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A542a0