

View Online at <https://aerobasegroup.com/nsn/4720-00-879-3018>

Cross Sectional Shape:

Round

Inside Diameter:

Between 0.860 inches and 0.906 inches

Temperature Rating:

-65.0 degrees fahrenheit and 250.0 degrees fahrenheit single response

Outside Diameter:

Between 1.282 inches and 1.344 inches

Minimum Inside Bending Radius:

10.500 inches

Connection Style:

Swivel nut with compression sleeve 1st end

End Connection Design:

Straight 2nd end

Connection Type:

Unthreaded external tube 2nd end

Burst Test Pressure:

4500.0 pounds per square inch

Layer Composition And Location:

1st layer braided steel wire and outer layer molded rubber

Maximum Operating Pressure:

1125.0 pounds per square inch

Hydrostatic Test Pressure:

2250.0 pounds per square inch

Outer Covering Environmental Protection:

Mildew resistant and oil resistant and oil resistant

Inside Surface Condition:

Smooth

Measuring Method And Length:

20.880 inches

Outside Diameter Tube Accommodated:

1.000 inches 2nd end

Media For Which Designed:

Fuel/oil, hydrocarbon single response

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A542a0