NSN 4720-00-879-4093

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-879-4093 **Cross Sectional Shape:** Round **Thread Class:** 3b 1st end **Thread Direction:** Right-hand 1st end **Inside Diameter:** 0.250 inches **Tempurature Rating:** -65.0 degrees celsius and 250.0 degrees celsius single response **Outside Diameter:** 0.578 inches **Connection Style:** Swivel nut flare 1st end **End Connection Design:** Straight 1st end **Connection Type:** Threaded internal tube 1st end Thready Qty Per Inch (tpi): 20 1st end **Burst Test Pressure:** 10000.0 pounds per square inch **Layer Composition And Location:** 1st layer braided polyamide cord and 2nd layer braided wire and outer layer rubber impregnated braided cotton cord **Maximum Operating Pressure:** 3000.0 pounds per square inch **Thread Size:** 0.500 inches 1st end Seat Angle: 37.0 degrees 1st end **Hydrostatic Test Pressure:** 5000.0 pounds per square inch **Inside Surface Condition:** Smooth **Measuring Method And Length:** 55.500 inches **Thread Series Designator:** Unf 1st end Shelf Life: N/a

Unit Of Measure:

NSN 4720-00-879-4093

Nonmetallic Hose Assembly - Page 2 of 2



Demilitarization:

No

Fiig:

A542a0