## NSN 4720-00-880-0349

**Cross Sectional Shape:** 

Nuts drilled for safety wire

Round

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-880-0349

Measuring Method And Length:
Smooth
Inside Surface Condition:
90.0 degrees 1st end
Flow Angle:
3000.0 pounds per square inch
Hydrostatic Test Pressure:
37.0 degrees 1st end
Seat Angle:
0.562 inches 1st end
Thread Size:
1500.0 pounds per square inch
Maximum Operating Pressure:
Outer layer braided corrosion resistant steel wire
Layer Composition And Location:
12000.0 pounds per square inch
Burst Test Pressure:
Electrostatic discharge capability
Features Provided:
Threaded internal tube 1st end
Connection Type:
Elbow 1st end
End Connection Design:
Swivel nut flare 1st end
Connection Style:
315.0
Angle Between Rigid Elbow Fittings In Deg:
0.438 inches
Outside Diameter:
-65.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response
Tempurature Rating:
0.312 inches
Inside Diameter:
Right-hand 1st end
Thread Direction:
3b 1st end
Thread Class:

## NSN 4720-00-880-0349

Nonmetallic Hose Assembly - Page 2 of 2



Thread Series Designator:
Unf 1st end
Specification Data:
07482-j267d0051d315b manufacturers source control
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A542a0