NSN 4720-00-880-3215

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-880-3215

Cross Sectional Shape:
Round
Thread Direction:
Right-hand 1st end Inside Diameter:
0.375 inches
Tempurature Rating:
-40.0 degrees fahrenheit and 275.0 degrees fahrenheit single response
Outside Diameter:
0.750 inches
Minimum Inside Bending Radius:
1.750 inches
End Application:
Clark model 290m; tractor, wheeled, ind., diesel driven; med dbp, nsn 2420000889384, w/rops nsn 2420010590090
Connection Style:
Inverted flare 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded external pipe 1st end
Burst Test Pressure:
900.0 pounds per square inch
Layer Composition And Location:
1st layer rubber impregnated cotton fabric and 2nd layer rubber impregnated cotton fabric and outer layer molded rubber
Maximum Operating Pressure:
225.0 pounds per square inch
Thread Size:
0.250 inches 1st end
Seat Angle:
30.0 degrees 1st end
Hydrostatic Test Pressure:
450.0 pounds per square inch
Outer Covering Environmental Protection:
Oil resistant and ozone resistant
Inside Surface Condition:
Smooth
Measuring Method And Length:
25.000 inches
Special Features:
Fittings are permanently attached
Media For Which Designed:

Air single response

NSN 4720-00-880-3215

Nonmetallic Hose Assembly - Page 2 of 2



Inread	Series	Designator
Nptf 1st	end	

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0