## NSN 4720-00-880-6722

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-880-6722

Cross Sectional Shape:		
Round		
Thread Class:		
3b 1st end		
Thread Direction:		
Right-hand 1st end		
Inside Diameter:		
0.219 inches		
Tempurature Rating:		
-67.0 degrees fahrenheit and 400.0 degrees fahrenheit single response		
Outside Diameter:		
0.469 inches		
Minimum Inside Bending Radius:		
3.000 inches		
Exterior Color:		
Natural		
Connection Style:		
Swivel nut flare 1st end		
End Connection Design:		
Straight 1st end		
Connection Type:		
Threaded internal tube 1st end		
Features Provided:		
Electrostatic discharge capability		
Burst Test Pressure:		
16000.0 pounds per square inch		
Layer Composition And Location:		
1st layer braided steel wire and 2nd layer woven cotton cord and outer layer braided corrosion resistant steel wire		
Maximum Operating Pressure:		
3000.0 pounds per square inch		
Thread Size:		
0.438 inches 1st end		
Seat Angle:		
37.0 degrees 1st end		
Hydrostatic Test Pressure:		
6000.0 pounds per square inch		
Outer Covering Environmental Protection:		
Corrosion resistant		
Inside Surface Condition:		
Smooth		
Measuring Method And Length:		

11.875 inches

## NSN 4720-00-880-6722

Nonmetallic Hose Assembly - Page 2 of 2



Thread	Series	<b>Designator:</b>
--------	--------	--------------------

Unf 1st end

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A542a0