Nonmetallic Hose Assembly - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4720-00-880-7076

|    | cross Sectional Shape:   |
|----|--|
|    | tound  |
|    | hread Direction:   |
| R  | light-hand 1st end   |
| lr | nside Diameter:  |
| 0  | .375 inches  |
| Т  | empurature Rating:   |
| -4 | 40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response |
| С  | Connection Style:  |
| S  | wivel, plain 2nd end   |
| E  | ind Connection Design:   |
| S  | traight 2nd end  |
| С  | Connection Type:   |
| Т  | hreaded external pipe 2nd end  |
| B  | Burst Test Pressure:   |
| 1  | 1000.0 pounds per square inch  |
| L  | ayer Composition And Location:                                       |
| 1  | st layer braided steel wire and outer layer molded rubber, synthetic |
| N  | laximum Operating Pressure:  |
| 2  | 750.0 pounds per square inch   |
| Т  | hread Size:  |
| 0  | .250 inches 2nd end  |
| S  | eat Angle:   |
| 3  | 7.0 degrees 1st end  |
| Ir | nside Surface Condition:   |
| S  | Smooth   |
| N  | leasuring Method And Length:   |
| 9  | 4.000 inches   |
| N  | ledia For Which Designed:  |
| F  | uel/oil, hydrocarbon single response                                 |
| Т  | hread Series Designator:   |
| Ν  | lpt 1st end  |
| S  | shelf Life:  |
| Ν  | l/a  |
| U  | Init Of Measure:   |
|    |  |
| D  | Demilitarization:  |
| Ν  | lo   |
| F  | iig:   |
| Δ  | .542a0   |