## NSN 4720-00-880-7702

**Cross Sectional Shape:** 

16.500 inches working

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-880-7702

Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.406 inches
Tempurature Rating:
-65.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response
Outside Diameter:
0.562 inches
Minimum Inside Bending Radius:
4.625 inches
Connection Style:
Swivel nut, flareless 2nd end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Features Provided:
Electrostatic discharge capability and reusable end fittings
Burst Test Pressure:
8000.0 pounds per square inch
Layer Composition And Location:
Outer layer braided corrosion resistant steel wire
Maximum Operating Pressure:
1500.0 pounds per square inch
Thread Size:
0.750 inches 2nd end
Seat Angle:
12.0 degrees 2nd end
Hydrostatic Test Pressure:
3000.0 pounds per square inch
Flow Angle:
90.0 degrees 2nd end
Vacuum In Torr:
50.8
Inside Surface Condition:
Smooth
Measuring Method And Length:

## NSN 4720-00-880-7702

Nonmetallic Hose Assembly - Page 2 of 2



Throad	Carias	Decimates
illieau	oenes	Designator:

Unf 2nd end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0