Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-881-0031

| Cross Sectional Shape: | |
|---|---|
| Round | |
| Thread Class: | |
| 3b 1st end | |
| Thread Direction: | |
| Right-hand 1st end | |
| Inside Diameter: | |
| 1.125 inches | |
| Tempurature Rating: | |
| -65.0 degrees fahrenheit and 250.0 degrees fahrenheit single response | |
| Outside Diameter: | |
| 1.437 inches | |
| Minimum Inside Bending Radius: | |
| 8.000 inches | |
| Connection Style: | |
| Swivel nut, flareless 1st end | |
| End Connection Design: | |
| Straight 1st end | |
| Connection Type: | |
| Threaded internal tube 1st end | |
| Thready Qty Per Inch (tpi): | |
| 12 1st end | |
| Burst Test Pressure: | |
| 2000.0 pounds per square inch | |
| Layer Composition And Location: | |
| 1st layer braided corrosion resistant steel wire and outer layer braided corrosion resistant steel wire | 3 |
| Maximum Operating Pressure: | |
| 500.0 pounds per square inch | |
| Thread Size: | |
| 1.625 inches 1st end | |
| Seat Angle: | |
| 12.0 degrees 1st end | |
| Hydrostatic Test Pressure: | |
| 1300.0 pounds per square inch | |
| Inside Surface Condition: | |
| Smooth | |
| Measuring Method And Length: | |
| 69.750 inches working | |
| Media For Which Designed: | |
| Fuel/oil, hydrocarbon single response | |
| Thread Series Designator: | |
| Unf 1st end | |
| | |

Nonmetallic Hose Assembly - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A542a0

